

Product number of the basic variant	Description/Designation	Capacity in pairs	LSA-PLUS	Drop wire	LSA-NT	Back-mount frame	PROFIL technology	Is wall mounting possible	Pole mounting by means of:	Protection in acc. with DIN 40050	Cable feed-in from:	Locked by means of:	Temperature range in °C	Box material and flammability
6430 1 002-00	Kronection Box A-2	max 2	2 pairs	No	No	BR 8	No	Yes	screws	IP 54	below	Snap-in	-30 80	Duroplast / GFK UL 94 V0
6431 1 002-00	Kronection Box A-6	max 6	6 pairs	No	No	BR 8	No	Yes	screws	IP 54	below	Snap-in slotted screw	-30 80	Duroplast / GFK UL 94 V0
6432 1 002-00	Kronection Box A-10	max10	10 pairs	No	No	BR 8	No	Yes	screws or mounting strap	IP 54	below	Snap-in Slotted screw Cylinder lock	-30 80	Duroplast / GFK UL 94 V0
6751 1 123-xx	Kronection DT plus 10	max 10	No	12 pairs	No	No	No	Yes	screws or mounting strap	IP54	below	Snap-in Snap-in	-30 80	Polyester / PP UL 94 V0
6541 1 002-00	Kronection Box A-30	max 30	30 pairs	10 pairs	not very suitable	Yes	Yes	Yes	screws or mounting strap	IP55	below	Snap-in Lock with lock mechanism 19	-30 80	Duroplast / GFK UL 94 V0
6838 1 001-00	Kronection Box A-50U Box A-200U	max 50 max 200	50 pairs 200 pairs	No 40 pairs	Yes Yes	Yes Yes	Yes	Yes	only flush mounting	IP54	below & above	Turnbuckle or Cylinder lock	-25 60	Polyester / PP UL 94 HB
6542 1 002-00	Kronection Box A-100	max 120	100 pairs	20 pairs	120 pairs	Yes	Yes	Yes	screws or mounting strap	IP54	below	Snap-in Lock with lock mechanism	-40 80	Duroplast / GFK UL 94 V0
0416 1 003-50	Kronection Box A-200	max 300	200 pairs	40 pairs	300 pairs	Yes	Yes	Yes	screws or mounting strap	IP54	below	turnbuckle or cylinder lock	-30 80	Polyester resin UL 94 V0
7016 1 103-00	UNI-Box size I	max 30	30 pairs	4 pairs	30 pairs	Yes	Yes	Yes	screws or mounting strap	IP54	below	Cylinder lock Padlock	-20 80	PBT UL 94 V0
7016 1 203-00	UNI-Box size II	max 60	50 pairs	10 pairs	60 pairs	Yes	Yes	Yes	screws or mounting strap	IP54	below	Cylinder lock Padlock	-20 80	PBT UL 94 V0
7016 1 303-00	UNI-Box size III	max. 120	100 pairs	20 pairs	120 pairs	Yes	Yes	Yes	screws or mounting strap	IP54	below	Cylinder lock Padlock	-20 80	PBT UL 94 V0
7016 1 403-00	UNI-Box size IV	max 200	150 pairs	30 pairs	200 pairs	Yes	Yes	Yes	screws or mounting strap	IP54	below	Cylinder lock Padlock	-20	PBT UL 94 V0